

Trade name: edding UV-Ink contained in: edding 8280 securitas uv-marker

Current version : 2.1.1, issued: 01.02.2017

Replaced version: 2.1.0, issued: 14.03.2012

Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

edding UV-Ink contained in: edding 8280 securitas uv-marker

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Ink for use in drawliners

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

edding International GmbH

Bookkoppel 7

D-22926 Ahrensburg

Telephone no. +49 (0) 41 02 / 80 8-0

Information provided by / telephone

+49 (0)4102 - 808-0

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)30 30686 790 (Giftnotruf Berlin)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Acute Tox. 4; H332

Eye Irrit. 2; H319

Flam. Liq. 2; H225

Skin Irrit. 2; H315

STOT RE 2; H373

STOT SE 3; H335

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms



GHS02



GHS07



GHS08

Signal word

Danger

Trade name: edding UV-Ink contained in: edding 8280 securitas uv-marker

Current version : 2.1.1, issued: 01.02.2017

Replaced version: 2.1.0, issued: 14.03.2012

Region: GB

Hazardous component(s) to be indicated on label:

xylene

Hazard statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapours.
P271	Use only outdoors or in a well-ventilated area.
P370+P378	In case of fire: Use water spray, extinguishing powder, foam or CO2 to extinguish.
P405	Store locked up.
P501	Dispose of contents/container to a facility in accordance with local and national regulations.

2.3 Other hazards

No data available.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Chemical characterization

Mixture (preparation)

Trade name: edding UV-Ink contained in: edding 8280 securitas uv-marker

Current version : 2.1.1, issued: 01.02.2017

Replaced version: 2.1.0, issued: 14.03.2012

Region: GB

Hazardous ingredients

No	Substance name		Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration	%
1	xylene			
	1330-20-7 215-535-7 601-022-00-9 -	STOT RE 2; H373 Flam. Liq. 3; H226 Asp. Tox. 1; H304 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 Acute Tox. 4; H332	< 30.00	%-b.w.
2	2-butoxyethyl acetate			
	112-07-2 203-933-3 607-038-00-2 -	Acute Tox. 4*; H312 Acute Tox. 4*; H332	< 20.00	%-b.w.
3	1-methoxy-2-propanol			
	107-98-2 203-539-1 603-064-00-3 -	Flam. Liq. 3; H226 STOT SE 3; H336	< 10.00	%-b.w.
4	cyclohexanone			
	108-94-1 203-631-1 606-010-00-7 -	Acute Tox. 4*; H332 Flam. Liq. 3; H226	< 10.00	%-b.w.
5	ethanol		pls. refer to footnote (1)	
	64-17-5 200-578-6 603-002-00-5 -	Flam. Liq. 2; H225 Eye Irrit. 2; H319	< 10.00	%-b.w.
6	ethylbenzene			
	100-41-4 202-849-4 601-023-00-4 -	Acute Tox. 4*; H332 Asp. Tox. 1; H304 Flam. Liq. 2; H225 STOT RE 2; H373	< 10.00	%-b.w.
7	2,5-thiophenediylbis(5-tert-butyl-1,3-benzoxazole)			
	7128-64-5 230-426-4 - -	Aquatic Chronic 4; H413	< 5.00	%-b.w.

Full Text for all H-phrases and EUH-phrases: pls. see section 16

(*; **; ***; ****) Detailed explanation pls. refer to CLP regulation No. 1272/2008, annex VI, 1.2

(1) Aberrant from/in addition to the classification set out in Annex VI, this substance is classified according to European Regulation (EC) No 1272/2008 (CLP), Article 4 (3), paragraph 2.

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
1	C	-	-	-
5	-	Eye Irrit. 2; H319: C >= 50%	-	-

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

No	Route, target organ, concrete effect
6	H373 -; hearing organs; - H373 -; hearing organs; -

Trade name: edding UV-Ink contained in: edding 8280 securitas uv-marker

Current version : 2.1.1, issued: 01.02.2017

Replaced version: 2.1.0, issued: 14.03.2012

Region: GB

3.3 Other information

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

After inhalation

Ensure supply of fresh air.

After skin contact

Wash off immediately with soap and water.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

After ingestion

Rinse mouth thoroughly with water. Call a doctor immediately. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam; Extinguishing powder; Water spray jet; Carbon dioxide

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO₂); Carbon monoxide (CO)

5.3 Advice for firefighters

Use self-contained breathing apparatus. Cool endangered containers with water spray jet. Wear protective clothing. Suppress gases/vapours/mists with water spray jet.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away sources of ignition.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). When picked up, treat material as prescribed under heading "Disposal considerations".

Trade name: edding UV-Ink contained in: edding 8280 securitas uv-marker

Current version : 2.1.1, issued: 01.02.2017

Replaced version: 2.1.0, issued: 14.03.2012

Region: GB

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Provide good ventilation at the work area (local exhaust ventilation, if necessary). If workplace exposure limits are exceeded, respiratory protection approved for this particular job must be worn. Product inherent handling risks must be minimised taking the appropriate measures for protection and preventive actions. The working process should be designed to rule out the release of hazardous substances or skin contact as far it is possible by the state of the art.

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Wash hands before breaks and after work. Provide eye wash fountain in work area. Have emergency shower available.

Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition. Use explosion-proof equipment/fittings and non-sparking tools.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight.

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original one.

Advice on storage assembly

Do not store together with: Oxidizing agents; Acids; Alkalis

7.3 Specific end use(s)

No data available.

Trade name: edding UV-Ink contained in: edding 8280 securitas uv-marker

Current version : 2.1.1, issued: 01.02.2017

Replaced version: 2.1.0, issued: 14.03.2012

Region: GB

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.	EC no.		
1	xylene	1330-20-7	215-535-7		
	List of approved workplace exposure limits (WELs) / EH40				
	Xylene, o-, m-, p- or mixed isomers				
	STEL	441	mg/m ³	100	ml/m ³
	TWA	220	mg/m ³	50	ml/m ³
	Skin resorption / sensibilisation		Sk		
	2000/39/EWG				
	Xylene, mixed isomers, pure				
	STEL	442	mg/m ³	100	ppm
	TWA	221	mg/m ³	50	ppm
Skin resorption / sensibilisation		Skin			
2	2-butoxyethyl acetate	112-07-2	203-933-3		
	2000/39/EWG				
	2-Butoxyethyl acetate				
	STEL	333	mg/m ³	50	ml/m ³
	TWA	133	mg/m ³	20	ml/m ³
	Skin resorption / sensibilisation		Skin		
	List of approved workplace exposure limits (WELs) / EH40				
	2-Butoxyethyl acetate				
	STEL			50	ml/m ³
	TWA			20	ml/m ³
Skin resorption / sensibilisation		Sk			
3	1-methoxy-2-propanol	107-98-2	203-539-1		
	2000/39/EWG				
	1-Methoxypropanol-2				
	STEL	568	mg/m ³	150	ml/m ³
	TWA	375	mg/m ³	100	ml/m ³
	Skin resorption / sensibilisation		Skin		
	List of approved workplace exposure limits (WELs) / EH40				
	1-Methoxypropan-2-ol				
	STEL	560	mg/m ³	150	ml/m ³
	TWA	375	mg/m ³	100	ml/m ³
Skin resorption / sensibilisation		Sk			
4	cyclohexanone	108-94-1	203-631-1		
	2000/39/EWG				
	Cyclohexanone				
	STEL	81.6	mg/m ³	20	ml/m ³
	TWA	40.8	mg/m ³	10	ml/m ³
	Skin resorption / sensibilisation		Skin		
	List of approved workplace exposure limits (WELs) / EH40				
	Cyclohexanone				
	STEL			20	ml/m ³
	TWA			10	ml/m ³
Skin resorption / sensibilisation		Sk			
5	ethanol	64-17-5	200-578-6		
	List of approved workplace exposure limits (WELs) / EH40				
	Ethanol				
TWA	1920	mg/m ³	1000	ml/m ³	
6	ethylbenzene	100-41-4	202-849-4		
	2000/39/EWG				
	Ethylbenzene				
STEL	884	mg/m ³	200	ml/m ³	
TWA	442	mg/m ³	100	ml/m ³	

Trade name: edding UV-Ink contained in: edding 8280 securitas uv-marker

Current version : 2.1.1, issued: 01.02.2017

Replaced version: 2.1.0, issued: 14.03.2012

Region: GB

	Skin resorption / sensibilisation	Skin		
List of approved workplace exposure limits (WELs) / EH40				
Ethylbenzene				
	STEL	552	mg/m ³	125 ml/m ³
	TWA	441	mg/m ³	100 ml/m ³
	Skin resorption / sensibilisation	Sk		

8.2 Exposure controls

Appropriate engineering controls

No data available.

Personal protective equipment

Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

Eye / face protection

Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material	butyl rubber		
Material thickness		0.5	mm
Breakthrough time	>	240	min.

Other

Normal chemical work clothing.

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form/Colour				
liquid				
colourless				
Odour				
characteristic				
Odour threshold				
No data available				
pH value				
Value	appr.	6.5		
Boiling point / boiling range				
Value	>	70	°C	
Reference pressure		1013	hPa	
Melting point / melting range				
No data available				
Decomposition point / decomposition range				
No data available				
Flash point				
Value	<	21	°C	

Trade name: edding UV-Ink contained in: edding 8280 securitas uv-marker

Current version : 2.1.1, issued: 01.02.2017

Replaced version: 2.1.0, issued: 14.03.2012

Region: GB

Auto-ignition temperature	
No data available	

Oxidising properties	
No data available	

Explosive properties	
No data available	

Flammability (solid, gas)	
No data available	

Lower flammability or explosive limits	
No data available	

Upper flammability or explosive limits	
No data available	

Vapour pressure			
Value	<	1100	hPa
Reference temperature		50	°C

Vapour density	
No data available	

Evaporation rate	
No data available	

Relative density	
No data available	

Density			
Value	0.80	-	1.00 g/cm ³
Reference temperature			20 °C

Solubility in water	
No data available	

Solubility(ies)	
No data available	

Partition coefficient: n-octanol/water	
No data available	

Viscosity			
Value	10	-	20 sec
Reference temperature			20 °C
Type	Efflux time		
Method	DIN cup 4 mm		

Solvent separation test			
Value	<	3	%
Reference temperature		20	°C

9.2 Other information

Other information	
The physical data is that of the main component/s.	

Trade name: edding UV-Ink contained in: edding 8280 securitas uv-marker

Current version : 2.1.1, issued: 01.02.2017

Replaced version: 2.1.0, issued: 14.03.2012

Region: GB

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available.

10.2 Chemical stability

No data available.

10.3 Possibility of hazardous reactions

No data available.

10.4 Conditions to avoid

None, if handled according to intended use.

10.5 Incompatible materials

Oxidizing agents; Acids; Alkalis

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	2-butoxyethyl acetate	112-07-2	203-933-3
	LD50	2400	mg/kg bodyweight
	Species	rat	
	Source	Manufacturer	
2	1-methoxy-2-propanol	107-98-2	203-539-1
	LD50	5660	mg/kg bodyweight
	Species	rat	
	Source	Manufacturer	

Acute dermal toxicity (result of the ATE calculation for the mixture)	
No	Product Name
1	edding UV-Ink contained in: edding 8280 securitas uv-marker
Remarks	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE dermal > 2000 mg/kg).

Acute dermal toxicity			
No	Substance name	CAS no.	EC no.
1	2-butoxyethyl acetate	112-07-2	203-933-3
	LD50	1580	mg/kg bodyweight
	Species	rabbit	
	Source	Manufacturer	
2	1-methoxy-2-propanol	107-98-2	203-539-1
	LD50	9999.99	mg/kg bodyweight
	Species	rabbit	
	Source	Manufacturer	

Trade name: edding UV-Ink contained in: edding 8280 securitas uv-marker

Current version : 2.1.1, issued: 01.02.2017

Replaced version: 2.1.0, issued: 14.03.2012

Region: GB

Acute inhalational toxicity (result of the ATE calculation for the mixture)	
No	Product Name
1	edding UV-Ink contained in: edding 8280 securitas uv-marker
ATE (Mixture)	15.8046
Route of exposure / physical from Method	Vapour
Remarks	Calculation method according Regulation (EC) No 1272/2008, (CLP), annex I, part 3, section 3.1.3.6. The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE for inhalation: > 20.000 ppmV (gases), > 20 mg/l (vapours), > 5 mg/l (dusts/mists).

Acute inhalational toxicity
No data available

Skin corrosion/irritation
No data available

Serious eye damage/irritation
No data available

Respiratory or skin sensitisation
No data available

Germ cell mutagenicity
No data available

Reproduction toxicity
No data available

Carcinogenicity
No data available

STOT-single exposure			
No	Substance name	CAS no.	EC no.
1	xylene	1330-20-7	215-535-7
Route of exposure	inhalational		
Target organ	respiratory tract		
Evaluation/classification	Based on available data, the classification criteria are met.		

STOT-repeated exposure
No data available

Aspiration hazard
No data available

Delayed and immediate effects as well as chronic effects from short and long-term exposure
Inhalation of solvent vapours in higher concentration may lead to nausea, headache, drowsiness and dizziness. When inhaled in larger quantities, the solvent vapours cause a narcotic effect. Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin.

Trade name: edding UV-Ink contained in: edding 8280 securitas uv-marker

Current version : 2.1.1, issued: 01.02.2017

Replaced version: 2.1.0, issued: 14.03.2012

Region: GB

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish (acute)
No data available
Toxicity to fish (chronic)
No data available
Toxicity to Daphnia (acute)
No data available
Toxicity to Daphnia (chronic)
No data available
Toxicity to algae (acute)
No data available
Toxicity to algae (chronic)
No data available
Bacteria toxicity
No data available

12.2 Persistence and degradability

No data available.

12.3 Bioaccumulative potential

No data available.

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Other adverse effects

No data available.

12.7 Other information

Other information
Ecological data are not available. Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Residuals must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

Trade name: edding UV-Ink contained in: edding 8280 securitas uv-marker

Current version : 2.1.1, issued: 01.02.2017

Replaced version: 2.1.0, issued: 14.03.2012

Region: GB

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

Class	3
Classification code	F1
Packing group	II
Hazard identification no.	33
UN number	UN1263
Technical name	PAINT RELATED MATERIAL
Special Provision 640	640D
Tunnel restriction code	D/E
Label	3

14.2 Transport IMDG

Class	3
Packing group	II
UN number	UN1263
Proper shipping name	PAINT RELATED MATERIAL
EmS	F-E+S-E
Label	3

14.3 Transport ICAO-TI / IATA

Class	3
Packing group	II
UN number	UN1263
Proper shipping name	Paint related material
Label	3

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

No data available.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, PREPARATIONS AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annexe XVII.	No 3, 40
---	----------

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category:	P5b
--	-----

Trade name: edding UV-Ink contained in: edding 8280 securitas uv-marker

Current version : 2.1.1, issued: 01.02.2017

Replaced version: 2.1.0, issued: 14.03.2012

Region: GB

15.2 Chemical safety assessment

For this mixture a chemical safety assessment has not been carried out.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

EC Directives 2000/39/EC, 2006/15/EC, 2009/161/EU

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding chapter.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H336	May cause drowsiness or dizziness.
H413	May cause long lasting harmful effects to aquatic life.

Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)

C	Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
---	--

Department issuing safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.