



## APC Home/Office SurgeArrest 5 outlets with 5V, 2.4A 2 port USB Charger 230V UK

## PM5U-UK

Call for More Information 0800 2799254

• Includes: User manual

| Output            |                        |
|-------------------|------------------------|
| Number of Outlets | 5.0                    |
| Receptacle Style  | BS 1363 United Kingdom |

| Input                 |                 |
|-----------------------|-----------------|
| Nominal Input Voltage | 230V            |
| Input frequency       | 50 Hz +/- 5 Hz  |
| Input Connections     | BS1363A British |
| Cord Length           | 1.8meters       |
| Number of Power Cords | 1               |
| Maximum Input Current | 13.0A           |

| Surge Protection and Filtering |           |
|--------------------------------|-----------|
| Surge energy rating            | 918Joules |
| ts_nm_surge_response           | 1ns       |
| Peak Current Common Mode       | 24kAmps   |
| Peak Current Normal Mode       | 12kAmps   |

| Physical       |               |
|----------------|---------------|
| Maximum Height | 56MM, 5.6CM   |
| Maximum Width  | 385MM, 38.5CM |
| Maximum Depth  | 73MM, 7.3CM   |
| Net Weight     | 0.72KG        |

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.



| Physical   |                       |
|--|-----------------------|
| Shipping weight                                    | 0.83KG                |
| Shipping Height                                    | 58MM, 5.8CM           |
| Shipping Width                                     | 405MM, 40.5CM         |
| Shipping Depth                                     | 130MM, 13.0CM         |
| Color  | White                 |
| Master Carton Dimensions (Length x Width x Height) | 7188 x 9525 x 10871MM |
| Master Carton Units                                | 12.0                  |
| Master Carton Weight                               | 10.49                 |
| Units per Pallet                                   | 216.0                 |
| SCC Codes  | 10731304313851        |

| Environmental               |                           |
|-----------------------------|---------------------------|
| Operating Temperature       | 0 - 40 °C                 |
| Operating Relative Humidity | 0 - 90 %                  |
| Operating Elevation         | 0 - 3048meters            |
| Storage Temperature         | -5 - 40 °C                |
| Storage Relative Humidity   | 0 - 95 (Non-condensing) % |
| Storage Elevation           | 0 - 4572meters            |

| Conformance                 |  |
|-----------------------------|--|
| Approvals                   | CE   |
| Equipment protection policy | Lifetime : 50000 euros                           |
| Standard warranty           | Limited Lifetime (European Union countries only) |

| Sustainable Offer Status |           |
|--------------------------|-----------|
| RoHS                     | Compliant |

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.