

Rack PDU, Switched, 1U, 16A, 208/230V, (8)C13

AP7921B



£899.00*

Price inclusive of VAT

Call for More Information 0800 2799254

- This APC Switched Rack PDU power distribution unit has a wide range of standardized PDU features that increase network efficiency, manageability and functionality. The output and input connections are (8)C13. Network management capabilities allow you to configure and manage rack PDUs from remote locations. It has a local current monitoring display that gives a visible warning in case of an overload. The remote individual outlet control provides real-time monitoring of connected loads. It has a multi-tier user access that enables you to restrict unauthorized use of outlets. This rack has a single input power source making it easy to install.
- Includes: Installation guide, Rack mounting brackets, User manual

Output	
Nominal Output Voltage	208V, 230V
Maximum Total Current Draw	16
Output Connections	(8) IEC 60320 C13

Input	
Nominal Input Voltage	200V, 208V, 230V
Input frequency	50/60 Hz
Input Connections	IEC 60320 C20
Cord Length	2.5meters
Acceptable Input Voltage	200 - 240VAC
Number of Power Cords	1
Load Capacity	3680VA
Maximum Input Current	20A
Regulatory Derated Input Current (North America)	16A

Physical	
Maximum Height	44MM, 4.4CM
Maximum Width	445MM, 44.5CM
Maximum Depth	108MM, 10.8CM

*Prices are indicative

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Rack PDU, Switched, 1U, 16A, 208/230V, (8)C13 | AP7921B | Downloaded on 11/01/2022 (EST)

Physical	
Rack Height	1U
Net Weight	2.27KG
Shipping weight	3.45KG
Shipping Height	70MM, 7.0CM
Shipping Width	343MM, 34.3CM
Shipping Depth	470MM, 47.0CM
Color	Black

Environmental	
Operating Temperature	0 - 45 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0 - 15240meters

Conformance	
Approvals	CE, CSA, cUL listed, EN 55022 class A, EN 55024, EN 61000-3-2, EN 61000-3-3, GOST, IRAM, MIC, UL 60950, UL listed, VCCI, VDE
Standard warranty	2 years repair or replace

Sustainable Offer Status	
RoHS	Compliant

*Prices are indicative

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.