

# Dual Port Gigabit PCI Express Server Network Adapter Card - PCIe NIC

Product ID: ST1000SPEXD4



The ST1000SPEXD4 PCI Express Dual-Port Gigabit Network Card lets you add two gigabit Ethernet ports to a client, server or workstation through a single PCIe slot. Each port provides 10/100/1000 Mbps capable Ethernet and is fully compatible with IEEE 802.3/u/ab standards.

Suitable for any standard PCI Express-enabled system, the 2-port Ethernet card supports full-duplex flow control for maximum data transfer speeds of up to 2000 Mbps - an ideal 2-port NIC for setting up dual-homed, or multi-homed host configurations providing added security to corporate networks.

The dual-port server adapter is compliant with the PCIe 2.0 standard and features support for Jumbo Frames and 802.1q VLAN tagging as well as Wake on LAN (WoL). The adapter includes an optional low-profile / half-height bracket that can be used for installation into a standard or small form-factor computer chassis.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

### Certifications, Reports and Compatibility



### Applications

- Ideal for VM environments with multiple operating systems, requiring shared or dedicated NICs
- Provide redundant connectivity to ensure an uninterrupted network connection
- Configure a dual-homed proxy or gateway system for an added layer of security
- Specially designed for desktop PC clients, servers, and workstations with few PCI Express slots available

### Features

- Two 10/100/1000Mbps compatible RJ-45 Ethernet ports
- Up to 9K Jumbo Frame support
- Compatible with PCI Express Base Specification 2.0 (backward compatible with 1.0a/1.1)
- Fully Compliant with IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, and supports IEEE 802.1Q VLAN tagging, IEEE 802.1P Layer 2 Priority Encoding and IEEE 802.3x Full Duplex Flow Control
- Supports Microsoft NDIS5 Checksum Offload (IP, TCP, UDP) and Large send Offload
- Wake-on-LAN / Remote Wake-up support
- Configured with standard profile bracket, low profile/half-height bracket included
- Supports Pair Swap / Polarity / Skew Correction

<b>Hardware</b>	Warranty	2 Years
	Bus Type	PCI Express
	Card Type	Standard Profile (LP bracket incl.)
	Chipset ID	Realtek - RTL8111H ASMedia - ASM1182E
	Industry Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab PCI Express Base Specification 2.0
	Interface	RJ45 (Gigabit Ethernet)
	Port Style	Integrated on Card
	Ports	2
<b>Performance</b>	Auto MDIX	Yes
	Compatible Networks	10/100/1000 Mbps
	Full Duplex Support	Yes
	Jumbo Frame Support	9K max.
	Maximum Data Transfer Rate	2000 Mbps (full-duplex), 1000 Mbps (half-duplex)
	Promiscuous Mode	Yes
	Supported Protocols	IEEE 802.1Q VLAN tagging, IEEE 802.1P Layer 2 Priority Encoding and IEEE 802.3x Full Duplex Flow Control
<b>Connector(s)</b>	Connector Type(s)	1 - PCI Express x1 Male
	External Ports	2 - RJ-45 Female
<b>Software</b>	OS Compatibility	Windows® 2000, XP, Vista, 7, 8, 8.1, 10 Windows Server® 2003, 2008 R2, 2012, 2012 R2, 2016, 2019 Mac OS 10.4 to 10.9 Linux 2.4.x to 4.11.x <i>LTS Versions only</i>
<b>Special Notes / Requirements</b>	System and Cable Requirements	Available PCI Express slot
<b>Indicators</b>	LED Indicators	2 - Green - Link/Activity 2 - Yellow - Gigabit Mode
	<b>Environmental</b>	Humidity
	Operating Temperature	0°C to 70°C (32°F to 158°F)
	Storage Temperature	0°C to 100°C (32°F to 212°F)
<b>Physical Characteristics</b>	Product Height	4.7 in [12 cm]
	Product Length	3.6 in [92.6 mm]

	Product Width	0.7 in [18 mm]
	Weight of Product	1.9 oz [53 g]
<b>Packaging Information</b>	Package Height	1.2 in [30 mm]
	Package Length	5.6 in [14.3 cm]
	Package Width	6.7 in [17 cm]
	Shipping (Package) Weight	5 oz [142 g]
	<b>What's in the Box</b>	Included in Package
1 - Low Profile Bracket		
1 - Driver CD		
1 - Instruction Manual		

Product appearance and specifications are subject to change without notice.