

## 2U 16in Universal Vented Rack Mount Cantilever Shelf - Fixed Server Rack Cabinet Shelf - 50lbs / 22kg

Product ID: CABSHELFV



The CABSHELFV 2U 16in Depth Universal Vented Rack Mount Shelf lets you add a compact, 2U shelf to virtually any standard 19-inch server rack or cabinet with front mount options. This TAA compliant product adheres to the requirements of the US Federal Trade Agreements Act (TAA), allowing government GSA Schedule purchases.

Our vented rack shelves improve air flow and help to lower temperatures in the rack. Constructed using SPCC commercial grade cold-rolled steel, this durable fixed rack shelf can hold up to 22kg (50lbs) of equipment - a perfect solution for storing small, non-rackmount equipment, tools, peripherals or accessories in your rack to keep them readily accessible.

Backed by a StarTech.com Lifetime warranty.

### Certifications, Reports and Compatibility



### Applications

- Supply additional storage space for mission critical hardware and non-rack mount equipment
- For use with all 19" wide Server Racks and Cabinets

### Features

- 2U Vented Rackmount Shelf
- Fits all standard 19" server racks
- TAA compliant for GSA Schedule purchases
- Holds up to 22kg (50lbs)
- SPCC 1.6mm Cold-rolled steel construction
- Front mount design

<b>Hardware</b>	Warranty	Lifetime
	Airflow Rate	Vented
	Cable Management	No
	Frame Type	Steel
	Mounting Options	Front Mount (Front Only)
	U Height	2U
<b>Performance</b>	Weight Capacity (Stationary)	50 lb [22.6 kg]
<b>Physical Characteristics</b>	Color	Black
	Material	Steel
	Product Height	3.5 in [88 mm]
	Product Length	19 in [483 mm]
	Product Width	16 in [406 mm]
	Rail Thickness	0.1 in [1.6 mm]
	Weight of Product	5.7 lb [2.6 kg]
<b>Packaging Information</b>	Package Height	4.3 in [10.8 cm]
	Package Length	22.3 in [56.6 cm]
	Package Width	16.9 in [42.8 cm]
	Shipping (Package) Weight	7.5 lb [3.4 kg]
<b>What's in the Box</b>	Included in Package	1 - 2U Fixed Rack Shelf
		4 - M5 Screws
		4 - M5 Cage Nuts
		1 - Instruction Manual

Product appearance and specifications are subject to change without notice.