


40/44 Pin IDE to Compact Flash SSD Adapter

Product ID: IDE2CF



This IDE to Compact Flash SSD Adapter Card allows you to convert a single Compact Flash (CF type I/II) Card or MicroDrive into a bootable IDE Solid State Drive - a simple and convenient way to replace a IDE hard disk drive.

The adapter card makes it easy to build your own do-it-yourself SSD (requires CF card or Micro Drive), allowing you to take advantage of the benefits that Solid State storage has to offer. With no moving parts, an SSD is the ideal solution in work environments desiring the key properties of SSD's - low power consumption, no noise, shock resistance, fast access time and low operating temperatures providing cooler and quieter storage than a conventional hard disk drive. Plus, Solid State drives are less susceptible to atmospheric hazards (e.g. dust particles, atmospheric changes etc.), ensuring seamless performance regardless of environmental factors.

The adapter is equipped with both a 40 pin (3.5in Desktop HDD) IDE channel or a 44 pin (2.5in Notebook HDD) IDE channel. This unique multi interface board allows the adapter to be used in both regular and small form factor case designs, create a perfect solution for embedded systems.

Certifications, Reports and Compatibility



Applications

- Use a small CompactFlash card in place of an IDE hard drive for small embedded solutions
- Use a solid state CompactFlash card in place of a mechanical hard drive for better durability
- Reduce system noise and heat by running a CompactFlash card instead of a tradition hard drive

Features

- Supports Ultra DMA mode
- Compatible with CompactFlash Type I, Type II, and Micro Drives
- Power, activity, and card detection LED indicators
- Supports 40 and 44 pin IDE interfaces
- Configurable IDE jumper settings for master or slave mode

	Warranty	2 Years	
Performance	Memory Media Type	Compact Flash I Compact Flash II IBM Micro Drive	
	RAID	No	
	Connector(s)	Connector Type(s) 1 - CompactFlash (50 pin) Slot 1 - IDE (40 Pin, EIDE/PATA) Male 1 - IDE (44 Pin, EIDE/PATA, 2.5" HDD) Male	
Software	OS Compatibility	OS independent; No software or drivers required	
Special Notes / Requirements	System and Cable Requirements	40 or 44 pin IDE interface	
Indicators	LED Indicators	1 - Green - Activity 1 - Red - Power 1 - Yellow - Card Present	
	Environmental	Humidity	75% RH
		Operating Temperature	0°C to +50°C (32°F to +122°F)
	Storage Temperature	-10°C to +70°C (14°F to +158°F)	
Physical Characteristics	Color	Black	
	Product Height	0.5 in [1.3 cm]	
	Product Length	2.8 in [70 mm]	
	Product Width	2.5 in [63 mm]	
	Weight of Product	0.7 oz [21 g]	
Packaging Information	Package Height	1.3 in [32 mm]	
	Package Length	5.7 in [14.5 cm]	
	Package Width	6.8 in [17.3 cm]	
	Shipping (Package) Weight	2.5 oz [72 g]	
What's in the Box	Included in Package	1 - IDE to CompactFlash Adapter 1 - Instruction Manual	
	Compatible Drive Types	CFAST 2.0, 1.0	
	Number of Drives	1	

Product appearance and specifications are subject to change without notice.