

(A). Wire Pin Assignment and Wire Description:


CN.1	Signal Name	CN.2	COLOR
1	PWR_Vbus1	A4,B4,A9,B9 A5	RED
2	UTP_Dn	A7	WHITE
3	UTP_Dp	A6	GREEN
4	GND_PWRrt1	A1,B1,A12,B12	BLACK
SHELL		SHELL	BRAID

(B). Electrical Testing :

- Open/Short:100%. Testing Line-Process.
- HI-POT: 100V AC/0.1sec.
- Insulation Resistance: 10MΩ (MIN) 100V DC

ITEM	MATERIALS LIST & SPEC. DESCRIPTION	Q'TY
④	MOLDED TPE WHITE	/
③	USB 2.0 TYPE C MALE, (TERMINAL:GOLD PLATED, SHELL:NI-PLATED)	1PCS
②	USB 2.0 A TYPE C MALE, (TERMINAL:GOLD PLATED, SHELL:NI-PLATED)	1PCS
①	USB 2.0 CABLE [32AWG*2C+22AWG*1C+2E]+AB OD:3.1mm JACKET TPE WHITE	/

THIRD ANGLE PROJECTION



GENERAL NOTES

DIMENSIONS ARE IN MM - DO NOT SCALE
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION THAT IS PROPERTY OF STARTECH.COM

StarTech.com

PRODUCT ID	RUSB2AC2MW
DESCRIPTION	RUGGED USB 2.0 A TO C CABLE 2M - WHITE
REV: A	DO NOT SCALE
SHEET : 1	OF: 1
DATE:	03/17/2020