

Product datasheet

Specifications



Rack PDU 2G, Metered by Outlet with Switching, ZeroU, 32A, 230V, (21) C13 & (3) C19

AP8653

Overview

Presentation APC Metered by Outlet with Switching Rack Power Distribution Units (PDUs) enable advanced, user-customizable power control and individual outlet power metering. Remote outlet level controls allow power on/off functionality for power recycling to reboot locked-up equipment and to avoid unauthorized use of individual outlets. Power sequencing delays allow users to define the order in which to power up or down attached equipment. Avoid circuit overload during power recovery and extend uptime of critical equipment by prioritizing the load shedding. Current metering provides real-time remote monitoring of connected loads. Switched Rack PDUs include real power monitoring, a temperature/humidity sensor port, and locking IEC receptacles. User-defined alarms warn of potential circuit overloads before critical IT failures occur. Users can access, configure, and control Switched rack PDUs through secure Web, SNMP, or Telnet Interfaces and is complimented by APC Centralized Management platforms using InfraStruxure Central, Capacity Manager and Change Manager.

Lead Time Usually in Stock

Main

Main Input Voltage	200 V 208 V 230 V
Pdu Type	Metered outlet
Main Output Voltage	230 V
Input Connection Type	IEC 60309 32 A 2P + E
Number Of Rack Unit	0U
Cable Length	3.00 m
Number Of Cables	1
Provided Equipment	CAN port terminator Installation guide Rack mounting brackets Safety guide Serial configuration cable

Physical

Colour	Black
Height	182.9 cm
Width	5.6 cm
Depth	5.1 cm
Net Weight	8.23 kg
Mounting Location	Side
Mounting Preference	No preference
Mounting Mode	Rack-mounted

Usb Compatible	No
----------------	----

Mounting Position	Vertical
-------------------	----------

Input

Permissible Voltage	220...240 V
---------------------	-------------

Max Line Current	32 A
------------------	------

Input Current Limits	32 A
----------------------	------

Load Capacity	7400 VA
---------------	---------

Network Frequency	50/60 Hz
-------------------	----------

Output

Number Of Power Socket Outlets	21 IEC 60320 C13 3 IEC 60320 C19
--------------------------------	-------------------------------------

Conformance

Product Certifications	VDE
------------------------	-----

Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3
-----------	--

Environmental

Ambient Air Temperature For Operation	-5...60 °C
---------------------------------------	------------

Relative Humidity	5...95 %
-------------------	----------

Operating Altitude	0...10000 ft
--------------------	--------------

Ambient Air Temperature For Storage	-25...65 °C
-------------------------------------	-------------

Storage Relative Humidity	5...95 %
---------------------------	----------

Storage Altitude	0.00...15240.00 m
------------------	-------------------

Packing Units

Unit Type Of Package 1	PCE
------------------------	-----

Number Of Units In Package 1	1
------------------------------	---

Package 1 Height	203.8 cm
------------------	----------

Package 1 Width	16.2 cm
-----------------	---------

Package 1 Length	11.8 cm
------------------	---------

Package 1 Weight	10.5 kg
------------------	---------

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)



Energy Efficient Take-back Transparency

Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

Well-being performance

✓ Lead Free

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
