

Rack PDU, Metered, 1U, 16A, 208/230V, (8) C13



AP7821B

Overview

Lead Time Usually in Stock

Main	
Main Input Voltage	200 V 208 V 230 V
Pdu Type	Metered
Main Output Voltage	208 V 230 V
Input Connection Type	IEC 60320 C20
Number Of Rack Unit	1U
Cable Length	2.50 m
Provided Equipment	Cord retention bracket(s) Installation guide Rack mounting brackets User manual

Physical

Height	4.4 cm
Width	44.4 cm
Depth	10.2 cm
Net Weight	1.74 kg
Mounting Location	Front Rear
Mounting Preference	No preference
Mounting Mode	Rack-mounted
Mounting Position	Horizontal

Input

[In] Rated Current	16 A
Input Current Limits	20 A
Load Capacity	3300 VA
Network Frequency	50/60 Hz

Output

Number Of Power Socket Outlets 8 IEC 60320 C13

Conformance

Product Certifications	cUL listed	
	C-Tick	
	CE	
	CSA	
	GOST	
	UL listed	
	VCCI	
	VDE	
Standards	FCC part 15 class A	
	ICES-003	
	UL 60950	

Environmental

Ambient Air Temperature For Operation	-545 °C
Relative Humidity	595 %
Operating Altitude	010000 ft
Ambient Air Temperature For Storage	-2565 °C
Storage Relative Humidity	595 %
Storage Altitude	0.0015240.00 m

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6.4 cm
Package 1 Width	33.7 cm
Package 1 Length	47 cm
Package 1 Weight	2.92 kg

Contractual warranty

Warranty 2 years repair or replace



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Learn more about Green Premium >









Energy Efficient Take-back Transparency RoHS/REACh

Resource performance

Energy Efficient Product

Take-Back Program Available

Well-being performance

Mercury Free

Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation

Eu Rohs Directive

Compliant with Exemptions

Environmental Disclosure

Product Environmental Profile

Circularity Profile

End of Life Information